

A30 SPECIFICATIONS

SSD for System and Cache	480G M.2 NVMe
CPU	Intel N4200 Quad Core
Music Storage	10TB (3.5" HDD)
Power Supply	Full-Linear
Display	22 cm 1920 x 480 WIDE IPS LCD
Clock Structure	Revised Full Differential System
Main Clock Accuracy	OCXO Based Precision Jitter Reducing Clock Generator
Audio Dedicated USB Port	1 x USB AUDIO Class 2.0
Digital Audio Inputs	1 x RCA SPDIF / 1 x BNC SPDIF / 2 x TOSLINK up to 24-bit / 192 kHz
Data USB	2 x USB 3.0 (Rear)
Ethernet	1 x Double-Isolated Gigabit Ethernet
Analog Audio Outputs	Unbalanced (RCA): 2 or (2,7) Vrms / Balanced (XLR): 4 or (5,4) Vrms selectable
Headphone Outputs	1 x 4 pin XLR Balanced / 1 x 4.4mm Balanced / 1 x 1/4in Unbalanced
Volume Control	-90 dB - 0dB, 0.5 dB step, Velocity Sensitive Operation Variable output control from front panel rotary knob, Conductor App and supplied IR remote control when used as preamplifier
USB Audio Output	PCM: Up to 32bit / 768kHz DSD: DoP Up to 256, Native DSD Up to 512
DAC Chipset	AKM AK4497 Dual-Mono Design
CD Ripping	TEAC Slot-Load CD-ROM Drive, Automated ripping support for Arconova Nimbie Autoloader via USB 3.0 port (optional)
Internal UPS	Super Capacitor Based Internal UPS
Dimensions (WHD) & Weight	430 x 141 x 355 mm, 17 Kg